



STARDEK II Clear Sealer™

Technical Report

High Solids Acrylic Coating

Description:

STARDEK II Clear Sealer is a complex blend of Solvent Base Thermoplastic Acrylic Polymers supplied as a high solids coating. It is designed to withstand heavy traffic giving extreme durability plus easy maintenance. The dry film possess outstanding flexibility, toughness, and freedom from tack at elevated temperatures. Unlike some paints or stains, it has excellent resistance to tire marking, it is grease, oil and mildew resistant. With tough color pigmentation designed to withstand direct sunlight with minimal fading or oxidation. Over the last **THIRTY FIVE** years this coating has proven itself to be a far superior product regarding the properties mentioned above.

Benefits:

- Non - Ambering
- Excellent Color Stability
- Moisture Insensitivity
- Grease, Oil, Mildew Resistant
- No Clear Maintenance Coatings
- Comparatively Low Cost
- Hard durable surface
- Decorative long lasting finish

Packaging:

STARDEK II Clear Sealer is available in both 5 gallon and 1 gallon pails. Available in a wide range of colors.

Approximate Coverage:

Although coverage will vary from slab to slab **STARDEK II Clear Sealer** will cover approximately 175 sqft per gallon.

Test Results:

Chemical Resistance, 7 days	
Water Resistance	Excellent
Alkali Resistance	Excellent
Muriatic Acid Resistance	Excellent
Gasoline Resistance	Fair
Washability (ASTM D3450)	100%
Gloss 20°	35.1
Gloss 60°	73.7
Reflectance (brightness)	.90
Pencil Hardness	2H
Sward Rocker Hardness (7 days)	9

Storage and Handling:

Store **STARDEK II Clear Sealer** in a cool, dry area. Partial pails of **STARDEK II Clear Sealer** can be resealed for future use. If properly sealed, there will be no change in physical properties and effectiveness will not be impaired. Dispose of empty containers properly according to current local, State, and Federal regulations.

Shelf Life:

Average shelf life is twelve months from shipping date if stored properly.

Health and Hazard Information:

This material is considered a FLAMMABLE LIQUID. Use product with adequate ventilation and personal protection. MSDS available upon request.

Availability:

Product is available from Color-Crown Corporation or any of it's authorized distributors.

STARDEK® mfg. by:
Color-Crown Corporation
928 Sligh Ave.
Seffner, FL 33584
(800) 282-1599 ♦ FAX (813) 655-8830

The Choice of Professionals. . . .

The information contained herein is based on data obtained by our own research and other recognized manufacturers and is considered accurate. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. This information is furnished upon the condition that the person receiving it shall make his own tests to determine the suitability thereof for his particular purpose.